



**Recommendation ITU-R BT.1306-7**  
(06/2015)

**Error-correction, data framing, modulation  
and emission methods for digital  
terrestrial television broadcasting**

**BT Series**  
**Broadcasting service**  
**(television)**

## Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

## Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Annex 1 of Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

### Series of ITU-R Recommendations

(Also available online at <http://www.itu.int/publ/R-REC/en>)

Series	Title
<b>BO</b>	Satellite delivery
<b>BR</b>	Recording for production, archival and play-out; film for television
<b>BS</b>	Broadcasting service (sound)
<b>BT</b>	<b>Broadcasting service (television)</b>
<b>F</b>	Fixed service
<b>M</b>	Mobile, radiodetermination, amateur and related satellite services
<b>P</b>	Radiowave propagation
<b>RA</b>	Radio astronomy
<b>RS</b>	Remote sensing systems
<b>S</b>	Fixed-satellite service
<b>SA</b>	Space applications and meteorology
<b>SF</b>	Frequency sharing and coordination between fixed-satellite and fixed service systems
<b>SM</b>	Spectrum management
<b>SNG</b>	Satellite news gathering
<b>TF</b>	Time signals and frequency standards emissions
<b>V</b>	Vocabulary and related subjects

*Note: This ITU-R Recommendation was approved in English under the procedure detailed in Resolution ITU-R 1.*

Electronic Publication  
Geneva, 2015

© ITU 2015

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

## RECOMMENDATION ITU-R BT.1306-7

**Error-correction, data framing, modulation and emission methods  
for digital terrestrial television broadcasting**

(Question ITU-R 132-2/6)

(1997-2000-2005-2006-2009-03/2011-12/2011-2015)

**Scope**

This Recommendation defines error-correction, data framing, modulation and emission methods for the existing digital terrestrial television broadcasting systems.

The ITU Radiocommunication Assembly,

*considering*

- a) that digital terrestrial television broadcasting (DTTB) is being introduced in the VHF/UHF bands by some administrations from 1997;
- b) that DTTB should fit into existing 6, 7, 8 MHz channels intended for analogue television transmission;
- c) that it may be desirable to support the simultaneous transmission of a hierarchy of nested quality levels (including high definition television (HDTV)), standard definition TV (SDTV) and low definition TV (LDTV) within a single channel;
- d) that it may be necessary for DTTB services to coexist with existing analogue television transmissions for a temporary period;
- e) that many types of interference, including co-channel and adjacent channel, ignition noise, multipath and other signal distortions exist in the VHF/UHF bands;
- f) that commonalities with alternative media, such as cable and satellite, could be advantageous at the level of outer coding scheme;
- g) that it is necessary that the frame synchronization be capable of robustness in channels subject to transmission errors;
- h) that it is desirable that the frame structure be adapted to different bit rate channels;
- j) that both single carrier and multi-carrier modulation methods may be introduced;
- k) that it is desirable that there be maximum commonality of characteristics between systems;
- l) that it is desirable that there be maximum commonality between digital terrestrial television transmissions that are required to coexist with existing analogue television transmissions and those that are not;
- m) that with the rapid evolution of digital technologies, digital terrestrial TV systems, proposed at different times, open new attractive possibilities and services;
- n) that the selection of a modulation option needs to be based on specific conditions such as spectrum resource, policy, coverage requirements, existing network structure, reception conditions, type of service required, cost to the consumer and broadcasters,

*recommends*

- 1** that administrations wishing to introduce DTTB should use one of the families of error correction, framing, modulation and emission methods outlined in Annex 1.

## Annex 1

Table 1a) provides data for single carrier systems, Table 1b) provides data about multi-carrier systems, and Table 1c) provides data about multi-carrier systems with RF band segmentation, Table 1d) provides data about the combined single- and multi-carrier systems, and Table 1e) provides data about Time-domain synchronized multi-carrier system or TDS multi-carrier systems. Specifications for Systems A, B, C, D and E are found in Attachments 1, 2, 3, 4 and 5.

Selection guidelines for Systems A, B, C, D and E are described in Attachment 6 to Annex 1.

TABLE 1  
Parameters for DTTB transmission systems  
a) Single carrier systems

	Parameters	6 MHz	7 MHz	8 MHz
1	Used bandwidth	5.38 MHz (−3 dB)	6.00 MHz (−3 dB)	7.00 MHz (−3 dB)
2	Number of radiated carriers	1	1	1
3	Modulation method	8-VSB	8-VSB	8-VSB
4	Spectrum shaping function	Root raised cosine roll-off $R = 5.8\%$	Root raised cosine roll-off $R = 8.3\%$	Root raised cosine roll-off $R = 7.1\%$
5	Channel occupancy <sup>(17)</sup>	See Recommendation ITU-R BT.1206	–	–
6	Active symbol duration	92.9 ns	83.3 ns	71.4 ns
7	Overall symbol or segment duration	77.3 μs (segment)	69.3 μs (segment)	59.4 μs (segment)
8	Transmission frame duration	48.4 ms	43.4 ms	37.2 ms
9	Channel equalization			
10	Inner interleaving	12 (independently encoded streams interleaved in time)	24 (independently encoded streams interleaved in time)	28 (independently encoded streams interleaved in time)
	Inner channel	$R = 2/3$ trellis, concatenated $R = 1/2$ or $R = 1/4$ trellis	$R = 2/3$ trellis, concatenated $R = 1/2$ or $R = 1/4$ trellis	$R = 2/3$ trellis, concatenated $R = 1/2$ or $R = 1/4$ trellis
11	Outer channel Reed-Solomon (RS) code	RS (207,187, $T = 10$ ), concatenated RS (184,164, $T = 10$ )	RS (207,187, $T = 10$ ), concatenated RS (184,164, $T = 10$ )	RS (207,187, $T = 10$ ), concatenated RS (184,164, $T = 10$ )
12	Outer interleaving	52 segment convolutional byte interleaved, concatenated 46 segment byte interleaved	52 segment convolutional byte interleaved, concatenated 46 segment byte interleaved	52 segment convolutional byte interleaved, concatenated 46 segment byte interleaved
13	Data randomization/ Energy dispersal	16 bit PRBS	16 bit PRBS	16 bit PRBS

TABLE 1 (continued)

## a) Single carrier systems (end)

	Parameters	6 MHz	7 MHz	8 MHz
14	Time/frequency synchronization	Segment sync, pilot carrier	Segment sync, pilot carrier	Segment sync, pilot carrier
15	Frame synchronization	Frame sync	Frame sync	Frame sync
16	Data equalization	Frame sync, PN.511 and $3 \times$ PN.63	Frame sync, PN.511 and $3 \times$ PN.63	Frame sync, PN.511 and $3 \times$ PN.63
17	Transmission mode identification	Mode symbols in frame sync	Mode symbols in frame sync	Mode symbols in frame sync
18	Net data rate	Depending on modulation code rate 4.23-19.39 Mbit/s	Depending on modulation code rate 4.72-21.62 Mbit/s	Depending on modulation code rate 5.99-27.48 Mbit/s
19	Carrier-to-noise ratio in an additive white Gaussian noise (AWGN) channel	Depending on channel code, 15.19 dB, 9.2 dB, 6.2 dB <sup>(1), (2)</sup>	Depending on channel code, 15.19 dB, 9.2 dB, 6.2 dB <sup>(2)</sup>	Depending on channel code, 15.19 dB, 9.2 dB, 6.2 dB <sup>(2)</sup>

## b) Multi-carrier systems

	Parameters	6 MHz multi-carrier (OFDM)	7 MHz multi-carrier (OFDM)	8 MHz multi-carrier (OFDM)
1	Used bandwidth	5.71 MHz	6.66 MHz	7.61 MHz
2	Number of radiated carriers	1 705 (2k mode) <sup>(3)</sup> 3 409 (4k mode) 6 817 (8k mode)	1 705 (2k mode) <sup>(3)</sup> 3 409 (4k mode) 6 817 (8k mode)	1 705 (2k mode) <sup>(3)</sup> 3 409 (4k mode) 6 817 (8k mode)
3	Modulation mode	Constant coding and modulation (CCM)	Constant coding and modulation (CCM)	Constant coding and modulation (CCM)
4	Modulation method	QPSK, 16-QAM, 64-QAM, MR-16-QAM, MR-64-QAM <sup>(4)</sup>	QPSK, 16-QAM, 64-QAM, MR-16-QAM, MR-64-QAM <sup>(4)</sup>	QPSK, 16-QAM, 64-QAM, MR-16-QAM, MR-64-QAM <sup>(4)</sup>
5	Channel occupancy <sup>(17)</sup>	See Recommendation ITU-R SM.1541	See Recommendations ITU-R BT.1206 or ITU-R SM.1541	See Recommendations ITU-R BT.1206 or ITU-R SM.1541
6	Active symbol duration	298.67 $\mu$ s (2k mode) 597.33 $\mu$ s (4k mode) 1 194.67 $\mu$ s (8k mode)	256 $\mu$ s (2k mode) 512 $\mu$ s (4k mode) 1 024 $\mu$ s (8k mode)	224 $\mu$ s (2k mode) 448 $\mu$ s (4k mode) 896 $\mu$ s (8k mode)
7	Carrier spacing	3 348.21 Hz (2k mode) 1 674.11 Hz (4k mode) 837.05 Hz (8k mode)	3 906 Hz (2k mode) 1 953 Hz (4k mode) 976 Hz (8k mode)	4 464 Hz (2k mode) 2 232 Hz (4k mode) 1 116 Hz (8k mode)

TABLE 1 (continued)

## b) Multi-carrier systems (continued)

	Parameters	6 MHz multi-carrier (OFDM)	7 MHz multi-carrier (OFDM)	8 MHz multi-carrier (OFDM)
8	Guard interval duration	1/32, 1/16, 1/8, 1/4 of active symbol duration 9.33, 18.67, 37.33, 74.67 $\mu$ s (2k mode) 18.67, 37.33, 74.67, 149.33 (4k mode) 37.33, 74.67, 149.33, 298.67 $\mu$ s (8k mode)	1/32, 1/16, 1/8, 1/4 of active symbol duration 8, 16, 32, 64 $\mu$ s (2k mode) 16, 32, 64, 128 $\mu$ s (4k mode) 32, 64, 128, 256 $\mu$ s (8k mode)	1/32, 1/16, 1/8, 1/4 of active symbol duration 7, 14, 28, 56 $\mu$ s (2k mode) 14, 28, 56, 112 $\mu$ s (4k mode) 28, 56, 112, 224 $\mu$ s (8k mode)
9	Overall symbol duration	308.00, 317.33, 336.00, 373.33 $\mu$ s (2k mode) 616.00, 634.67, 672.00, 746.67 $\mu$ s (4k mode) 1 232.00, 1 269.33, 1 344.00, 1 493.33 $\mu$ s (8k mode)	264, 272, 288, 320 $\mu$ s (2k mode) 528, 544, 576, 640 $\mu$ s (4k mode) 1 048, 1 088, 1 152, 1 280 $\mu$ s (8k mode)	231, 238, 252, 280 $\mu$ s (2k mode) 462, 476, 504, 560 $\mu$ s (4k mode) 924, 952, 1 008, 1 120 $\mu$ s (8k mode)
10	Transmission frame duration	68 OFDM symbols. One super frame consists of 4 frames	68 OFDM symbols. One super-frame consists of 4 frames	68 OFDM symbols. One super-frame consists of 4 frames
11	Inner channel code	Convolutional code, mother rate 1/2 with 64 states. Puncturing to rate 2/3, 3/4, 5/6, 7/8	Convolutional code, mother rate 1/2 with 64 states. Puncturing to rate 2/3, 3/4, 5/6, 7/8	Convolutional code, mother rate 1/2 with 64 states. Puncturing to rate 2/3, 3/4, 5/6, 7/8
12	Inner interleaving	Bit interleaving, combined with native or in-depth <sup>(5)</sup> symbol interleaving	Bit interleaving, combined with native or in-depth <sup>(5)</sup> symbol interleaving	Bit interleaving, combined with native or in-depth <sup>(5)</sup> symbol interleaving
13	Outer channel Reed-Solomon (RS) code	RS (204,188, $T = 8$ )	RS (204,188, $T = 8$ )	RS (204,188, $T = 8$ )
14	Outer interleaving	Byte-wise convolutional interleaving, $I = 12$	Byte-wise convolutional interleaving, $I = 12$	Byte-wise convolutional interleaving, $I = 12$
15	Data randomization/energy dispersal	PRBS	PRBS	PRBS
16	Time/frequency synchronization	Pilot carriers <sup>(6)</sup>	Pilot carriers <sup>(6)</sup>	Pilot carriers <sup>(6)</sup>
17	IP outer channel code Reed-Solomon (RS) code	MPE-FEC RS (255,191) <sup>(7)</sup>	MPE-FEC RS (255,191) <sup>(7)</sup>	MPE-FEC RS (255,191) <sup>(7)</sup>
18	Receiver power consumption reduction	Time-slicing <sup>(8)</sup>	Time-slicing <sup>(8)</sup>	Time-slicing <sup>(8)</sup>



TABLE 1 (continued)

**b) Multi-carrier systems (end)**

	Parameters	6 MHz multi-carrier (OFDM)	7 MHz multi-carrier (OFDM)	8 MHz multi-carrier (OFDM)
19	Transmission parameter signalling (TPS) <sup>(9)</sup>	Carried by TPS pilot carriers	Carried by TPS pilot carriers	Carried by TPS pilot carriers
20	System transport stream format	MPEG-2 TS	MPEG-2 TS	MPEG-2 TS
21	Net data rate	Depending on modulation, code rate and guard interval (3.69-23.5 Mbit/s for non-hierarchical modes) <sup>(10)</sup>	Depending on modulation, code rate and guard interval (4.35-27.71 Mbit/s for non-hierarchical modes) <sup>(10)</sup>	Depending on modulation, code rate and guard interval (4.98-31.67 Mbit/s for non-hierarchical modes) <sup>(10)</sup>
22	Carrier-to-noise ratio in an AWGN channel	Depending on modulation and channel code. 3.1-20.1 dB <sup>(11)</sup>	Depending on modulation and channel code. 3.1-20.1 dB <sup>(11)</sup>	Depending on modulation and channel code. 3.1-20.1 dB <sup>(11)</sup>

**c) Multi-carrier systems with radio-frequency band segmentation<sup>(12)</sup>**

	Parameters	6 MHz multi-carrier (segmented OFDM)	7 MHz multi-carrier (segmented OFDM)	8 MHz multi-carrier (segmented OFDM)
1	Numbers of segments (Ns)	13 <sup>(13)</sup>	13 <sup>(13)</sup>	13 <sup>(13)</sup>
2	Segment bandwidth (Bws)	6 000/14 = 428.57 kHz	7 000/14 = 500 kHz	8 000/14 = 571.428 kHz
3	Used bandwidth (Bw)	Bw × Ns + Cs 5.575 MHz (Mode 1) 5.573 MHz (Mode 2) 5.572 MHz (Mode 3)	Bw × Ns + Cs 6.504 MHz (Mode 1) 6.502 MHz (Mode 2) 6.501 MHz (Mode 3)	Bw × Ns + Cs 7.434 MHz (Mode 1) 7.431 MHz (Mode 2) 7.430 MHz (Mode 3)
4	Number of radiated carriers	1 405 (Mode 1) 2 809 (Mode 2) 5 617 (Mode 3)	1 405 (Mode 1) 2 809 (Mode 2) 5 617 (Mode 3)	1 405 (Mode 1) 2 809 (Mode 2) 5 617 (Mode 3)
5	Modulation method	DQPSK, QPSK, 16-QAM, 64-QAM	DQPSK, QPSK, 16-QAM, 64-QAM	DQPSK, QPSK, 16-QAM, 64-QAM
6	Channel occupancy <sup>(17)</sup>	See Recommendations ITU-R BT.1206 or ITU-R SM.1541	See Recommendations ITU-R BT.1206 or ITU-R SM.1541	See Recommendations ITU-R BT.1206 or ITU-R SM.1541
7	Active symbol duration	252 μs (Mode 1) 504 μs (Mode 2) 1 008 μs (Mode 3)	216 μs (Mode 1) 432 μs (Mode 2) 864 μs (Mode 3)	189 μs (Mode 1) 378 μs (Mode 2) 756 μs (Mode 3)
8	Carrier spacing (Cs)	Bws/108 = 3.968 kHz (Mode 1) Bws/216 = 1.984 kHz (Mode 2) Bws/432 = 0.992 kHz (Mode 3)	Bws/108 = 4.629 kHz (Mode 1) Bws/216 = 2.314 kHz (Mode 2) Bws/432 = 1.157 kHz (Mode 3)	Bws/108 = 5.291 kHz (Mode 1) Bws/216 = 2.645 kHz (Mode 2) Bws/432 = 1.322 kHz (Mode 3)

TABLE 1 (continued)

c) Multi-carrier systems with radio-frequency band segmentation<sup>(12)</sup> (continued)

	Parameters	6 MHz multi-carrier (segmented OFDM)	7 MHz multi-carrier (segmented OFDM)	8 MHz multi-carrier (segmented OFDM)
9	Guard interval duration	1/4, 1/8, 1/16, 1/32 of active symbol duration 63, 31.5, 15.75, 7.875 $\mu$ s (Mode 1) 126, 63, 31.5, 15.75 $\mu$ s (Mode 2) 252, 126, 63, 31.5 $\mu$ s (Mode 3)	1/4, 1/8, 1/16, 1/32 of active symbol duration 54, 27, 13.5, 6.75 $\mu$ s (Mode 1) 108, 54, 27, 13.5 $\mu$ s (Mode 2) 216, 108, 54, 27 $\mu$ s (Mode 3)	1/4, 1/8, 1/16, 1/32 of active symbol duration 47.25, 23.625, 11.8125, 5.90625 $\mu$ s (Mode 1) 94.5, 47.25, 23.625, 11.8125 $\mu$ s (Mode 2) 189, 94.5, 47.25, 23.625 $\mu$ s (Mode 3)
10	Overall symbol duration	315, 283.5, 267.75, 259.875 $\mu$ s (Mode 1) 630, 567, 535.5, 519.75 $\mu$ s (Mode 2) 1 260, 1 134, 1 071, 1 039.5 $\mu$ s (Mode 3)	270, 243, 229.5, 222.75 $\mu$ s (Mode 1) 540, 486, 459, 445.5 $\mu$ s (Mode 2) 1 080, 972, 918, 891 $\mu$ s (Mode 3)	236.25, 212.625, 200.8125, 194.90625 $\mu$ s (Mode 1) 472.5, 425.25, 401.625, 389.8125 $\mu$ s (Mode 2) 945, 850.5, 803.25, 779.625 $\mu$ s (Mode 3)
11	Transmission frame duration	204 OFDM symbols	204 OFDM symbols	204 OFDM symbols
12	Inner channel code	Convolutional code, mother rate 1/2 with 64 states. Puncturing to rate 2/3, 3/4, 5/6, 7/8	Convolutional code, mother rate 1/2 with 64 states. Puncturing to rate 2/3, 3/4, 5/6, 7/8	Convolutional code, mother rate 1/2 with 64 states. Puncturing to rate 2/3, 3/4, 5/6, 7/8
13	Inner interleaving	Intra and inter segments interleaving (frequency interleaving). Symbolwise convolutional interleaving 0, 380, 760, 1 520 symbols (Mode 1) 0, 190, 380, 760 symbols (Mode 2) 0, 95, 190, 380 symbols (Mode 3) (time interleaving)	Intra and inter segments interleaving (frequency interleaving). Symbolwise convolutional interleaving 0, 380, 760, 1 520 symbols (Mode 1) 0, 190, 380, 760 symbols (Mode 2) 0, 95, 190, 380 symbols (Mode 3) (time interleaving)	Intra and inter segments interleaving (frequency interleaving). Symbolwise convolutional interleaving 0, 380, 760, 1 520 symbols (Mode 1) 0, 190, 380, 760 symbols (Mode 2) 0, 95, 190, 380 symbols (Mode 3) (time interleaving)
14	Outer channel code	RS (204,188, $T = 8$ )	RS (204,188, $T = 8$ )	RS (204,188, $T = 8$ )
15	Outer interleaving	Byte-wise convolutional interleaving, $I = 12$	Byte-wise convolutional interleaving, $I = 12$	Byte-wise convolutional interleaving, $I = 12$
16	Data randomization/ energy dispersal	PRBS	PRBS	PRBS
17	Time/frequency synchronization	Pilot carriers	Pilot carriers	Pilot carriers
18	Transmission and multiplexing configuration	Carried by TMCC pilot carriers	Carried by TMCC pilot carriers	Carried by TMCC pilot carriers



TABLE 1 (continued)

c) Multi-carrier systems with radio-frequency band segmentation<sup>(12)</sup> (end)

	Parameters	6 MHz multi-carrier (segmented OFDM)	7 MHz multi-carrier (segmented OFDM)	8 MHz multi-carrier (segmented OFDM)
19	Net data rate	Depending on number of segments, modulation, code rate, hierarchical structure and guard interval 3.65-23.2 Mbit/s	Depending on number of segments, modulation, code rate, hierarchical structure and guard interval 4.26-27.1 Mbit/s	Depending on number of segments, modulation, code rate, hierarchical structure and guard interval 4.87-31.0 Mbit/s
20	Carrier-to-noise ratio in an AWGN channel	Depending on modulation and channel code 5.0-23 dB <sup>(14)</sup>	Depending on modulation and channel code 5.0-23 dB <sup>(14)</sup>	Depending on modulation and channel code 5.0-23 dB <sup>(14)</sup>

## d) Single- and multi-carrier combined systems

	Parameters	6 MHz	7 MHz	8 MHz
1	Used bandwidth	5.67 MHz	6.62 MHz	7.56 MHz
2	Number of radiated carriers	1 (single-carrier mode) 3 780 (multi-carrier mode)	1 (single-carrier mode) 3 780 (multi-carrier mode)	1 (single-carrier mode) 3 780 (multi-carrier mode)
3	Modulation mode	Constant coding and modulation (CCM)	Constant coding and modulation (CCM)	Constant coding and modulation (CCM)
4	Modulation method	4-QAM-NR, 4-QAM, 16-QAM, 32-QAM, 64-QAM	4-QAM-NR, 4-QAM, 16-QAM, 32-QAM, 64-QAM	4-QAM-NR, 4-QAM, 16-QAM, 32-QAM, 64-QAM
5	Channel occupancy <sup>(17)</sup>	See Recommendation ITU-R BT.1206	See Recommendation ITU-R BT.1206	See Recommendation ITU-R BT.1206
6	Active symbol duration	0.176 $\mu$ s (single-carrier mode) 666.67 $\mu$ s (multi-carrier mode)	0.151 $\mu$ s (single-carrier mode) 571.43 $\mu$ s (multi-carrier mode)	0.132 $\mu$ s (single-carrier mode) 500 $\mu$ s (multi-carrier mode)
7	Carrier spacing	5.67 MHz (single-carrier mode) 1.5 kHz (multi-carrier mode)	6.62 MHz (single-carrier mode) 1.75 kHz (multi-carrier mode)	7.56 MHz (single-carrier mode) 2.0 kHz (multi-carrier mode)
8	Frame header duration	1/9, 1/6, 1/4 of frame body of the signal frame duration 74.07, 104.94, 166.67 $\mu$ s	1/9, 1/6, 1/4 of frame body of the signal frame duration 63.49, 89.95, 142.86 $\mu$ s	1/9, 1/6, 1/4 of frame body of the signal frame duration 55.56, 78.70, 125.00 $\mu$ s
9	Overall signal frame duration	740.74, 771.60, 833.33 $\mu$ s	634.92, 661.38, 714.29 $\mu$ s	555.56, 578.70, 625.00 $\mu$ s
10	Transmission frame duration	Day-frame of 24 hours, minute-frame of 60 s, super-frame of 166.7 ms, and signal-frames of 740.74, 771.60, 833.33 $\mu$ s	Day-frame of 24 hours, minute-frame of 60 s, super-frame of 142.8 ms, and signal-frames of 634.92, 661.38, 714.29 $\mu$ s	Day-frame of 24 hours, minute-frame of 60 s, super-frame of 125 ms, and signal-frames of 555.56, 578.70, 625.00 $\mu$ s
11	Inner channel LDPC code	0.4 (7 488, 3 008), 0.6 (7 488, 4 512), 0.8 (7 488, 6 016)	0.4 (7 488, 3 008), 0.6 (7 488, 4 512), 0.8 (7 488, 6 016)	0.4 (7 488, 3 008), 0.6 (7 488, 4 512), 0.8 (7 488, 6 016)
12	Inner interleaving in frequency domain	Inside one signal frame (multi-carrier mode)	Inside one signal frame (multi-carrier mode)	Inside one signal frame (multi-carrier mode)

TABLE 1 (continued)

**d) Single- and multi-carrier combined systems (end)**

	<b>Parameters</b>	<b>6 MHz</b>	<b>7 MHz</b>	<b>8 MHz</b>
13	Outer channel BCH code	BCH (762, 752) derived from BCH (1 023, 1 013)	BCH (762, 752) derived from BCH (1 023, 1 013)	BCH (762, 752) derived from BCH (1 023, 1 013)
14	Outer convolutional interleaving in time domain	Number of interleaving branches B = 52, interleaving depth M = 240, 720	Number of interleaving branches B = 52, interleaving depth M = 240, 720	Number of interleaving branches B = 52, interleaving depth M = 240, 720
15	Data randomization/energy dispersal	PRBS	PRBS	PRBS
16	Time/frequency synchronization	PN sequence as the frame header of signal frame <sup>(15)</sup>	PN sequence as the frame header of signal frame <sup>(15)</sup>	PN sequence as the frame header of signal frame <sup>(15)</sup>
17	System information	Carried by 36 system information symbol per signal frame	Carried by 36 system information symbol per signal frame	Carried by 36 system information symbol per signal frame
18	System transport stream format	MPEG-2 TS	MPEG-2 TS	MPEG-2 TS
19	Net data rate	Depending on modulation, code and frame header (3.610-24.436 Mbit/s)	Depending on modulation, code and frame header (4.211-28.426 Mbit/s)	Depending on modulation, code and frame header (4.813-32.486 Mbit/s)
20	Carrier-to-noise ratio in an AWGN channel	Depending on modulation and channel code. 2.5-22.0 dB <sup>(16)</sup>	Depending on modulation and channel code. 2.5-22.0 dB <sup>(16)</sup>	Depending on modulation and channel code. 2.5-22.0 dB <sup>(16)</sup>

**e) TDS Multi-carrier systems**

<b>No.</b>	<b>Parameters</b>		<b>6 MHz multi-carrier (OFDM)</b>	<b>7 MHz multi-carrier (OFDM)</b>	<b>8 MHz multi-carrier (OFDM)</b>
1	Used bandwidth		5.67 MHz with the roll off factor of 0.05, 5.83 MHz with the roll off factor of 0.025	6.62 MHz with the roll off factor of 0.05, 6.81 MHz with the roll off factor of 0.025	7.56 MHz with the roll off factor of 0.05, 7.78 MHz with the roll off factor of 0.025
2	Number of radiated carriers	4k mode	4 096	4 096	4 096
		8k mode	8 192	8 192	8 192
		32k mode	32 678	32 678	32 678
3	Modulation modes		Constant coding and modulation (CCM)/variable coding and modulation (VCM)		
4	Modulation method		QPSK, 16-APSK, 64-APSK, 256-/APSK specific for each Service Channel		
5	Channel occupancy <sup>(17)</sup>		See Recommendation ITU-R BT.1206		

TABLE 1 (continued)

## e) TDS Multi-carrier systems (continued)

No.	Parameters		6 MHz multi-carrier (OFDM)	7 MHz multi-carrier (OFDM)	8 MHz multi-carrier (OFDM)
6	Active symbol duration	4k mode	722.40 $\mu$ s with the roll off factor of 0.05, 702.17 $\mu$ s with the roll off factor of 0.025	619.20 $\mu$ s with the roll off factor of 0.05, 601.86 $\mu$ s with the roll off factor of 0.025	541.80 $\mu$ s with the roll off factor of 0.05, 526.63 $\mu$ s with the roll off factor of 0.025
		8k mode	1444.80 $\mu$ s with the roll off factor of 0.05, 1404.34 $\mu$ s with the roll off factor of 0.025	1238.40 $\mu$ s with the roll off factor of 0.05, 1203.72 $\mu$ s with the roll off factor of 0.025	1083.60 $\mu$ s with the roll off factor of 0.05, 1053.26 $\mu$ s with the roll off factor of 0.025
		32k mode	5779.19 $\mu$ s with the roll off factor of 0.05, 5617.37 $\mu$ s with the roll off factor of 0.025	4953.60 $\mu$ s with the roll off factor of 0.05, 4814.89 $\mu$ s with the roll off factor of 0.025	4334.40 $\mu$ s with the roll off factor of 0.05, 4213.03 $\mu$ s with the roll off factor of 0.025
7	Carrier spacing	4k mode	1 384 Hz with the roll off factor of 0.05, 1 424 Hz with the roll off factor of 0.025	1 615 Hz with the roll off factor of 0.05, 1 662 Hz with the roll off factor of 0.025	1 846 Hz with the roll off factor of 0.05, 1 899 Hz with the roll off factor of 0.025
		8k mode	692 Hz with the roll off factor of 0.05, 712 Hz with the roll off factor of 0.025	807 Hz with the roll off factor of 0.05, 831 Hz with the roll off factor of 0.025	923 Hz with the roll off factor of 0.05, 949 Hz with the roll off factor of 0.025
		32k mode	173 Hz with the roll off factor of 0.05, 178 Hz with the roll off factor of 0.025	202 Hz with the roll off factor of 0.05, 208 Hz with the roll off factor of 0.025	231 Hz with the roll off factor of 0.05, 237 Hz with the roll off factor of 0.025
8	Guard interval duration	4k mode (1/8, 1/4, 1/2)	90.3, 181, 361 $\mu$ s with the roll off factor of 0.05. 87.8, 176, 351 $\mu$ s with the roll off factor of 0.025	77.4, 155, 310 $\mu$ s with the roll off factor of 0.05. 75.2, 150, 301 $\mu$ s with the roll off factor of 0.025	67.7, 135, 271 $\mu$ s with the roll off factor of 0.05. 65.8, 132, 263 $\mu$ s with the roll off factor of 0.025
		8k mode (1/16, 1/8, 1/4)	90.3, 181, 361 $\mu$ s with the roll off factor of 0.05. 87.8, 176, 351 $\mu$ s with the roll off factor of 0.025	77.4, 155, 310 $\mu$ s with the roll off factor of 0.05. 75.2, 150, 301 $\mu$ s with the roll off factor of 0.025	67.7, 135, 271 $\mu$ s with the roll off factor of 0.05. 65.8, 132, 263 $\mu$ s with the roll off factor of 0.025
		32k mode (1/64, 1/32, 1/16)	90.3, 181, 361 $\mu$ s with the roll off factor of 0.05. 87.8, 176, 351 $\mu$ s with the roll off factor of 0.025	77.4, 155, 310 $\mu$ s with the roll off factor of 0.05. 75.2, 150, 301 $\mu$ s with the roll off factor of 0.025	67.7, 135, 271 $\mu$ s with the roll off factor of 0.05. 65.8, 132, 263 $\mu$ s with the roll off factor of 0.025

TABLE 1 (continued)

## e) TDS Multi-carrier systems (continued)

No.	Parameters		6 MHz multi-carrier (OFDM)	7 MHz multi-carrier (OFDM)	8 MHz multi-carrier (OFDM)
9	Overall symbol duration	4k mode	813, 903, 1 084 $\mu$ s with the roll off factor of 0.05. 790, 878, 1 053 $\mu$ s with the roll off factor of 0.025	679, 774, 929 $\mu$ s with the roll off factor of 0.05. 677, 752, 903 $\mu$ s with the roll off factor of 0.025	610, 677, 813 $\mu$ s with the roll off factor of 0.05. 592, 658, 790 $\mu$ s with the roll off factor of 0.025
		8k mode	1 535, 1 625, 1 806 $\mu$ s with the roll off factor of 0.05. 1 492, 1 580, 1 755 $\mu$ s with the roll off factor of 0.025	1 316, 1 393, 1 548 $\mu$ s with the roll off factor of 0.05. 1 279, 1 354, 1 505 $\mu$ s with the roll off factor of 0.025	1 151, 1 219, 1 354 $\mu$ s with the roll off factor of 0.05. 1 119, 1 185, 1 317 $\mu$ s with the roll off factor of 0.025
		32k mode	5 869, 5 960, 6 140 $\mu$ s with the roll off factor of 0.05. 5 705, 5 793, 5 968 $\mu$ s with the roll off factor of 0.025	5 031, 5 108, 5 263 $\mu$ s with the roll off factor of 0.05. 4 890, 4 965, 5 116 $\mu$ s with the roll off factor of 0.025	4 402, 4 470, 4 605 $\mu$ s with the roll off factor of 0.05. 4 279, 4 345, 4 467 $\mu$ s with the roll off factor of 0.025
10	Super frame duration		Super frame starts with super-frame synchronization channel and a control channel for service channel signalling. Each super-frame has configurable number of data signal frames, with maximum duration of 250 $\mu$ s		
11	Input stream format		Transport streams (TS)		
12	Channel coding		LDPC/BCH code with block size of 61 440 or 15 360 bits and code rates of 1/2, 2/3, 5/6		
13	Interleaving		Bit interleaving, bit permutation and time interleaving separately for each service channel		
14	Service Channel		Support for multiple service channels. Modulation, coding and time interleaving depth selectable separately for each service channel		
15	Data randomization/energy dispersal				
	Initial scan		Fast scan process with special super-frame synchronization channel		
16	Time/frequency synchronization		Super-frame synchronization channel and dual PN-MC symbols of each signal frame		
17	Multiple input single output (MISO)		An optional 2 $\times$ 1 MISO configuration with Alamouti coding in the space-frequency domain		
18	Receiver power consumption reduction		Service channels are organized in both time and frequency domains. When receiving a single service channel only the service channel signalling and relevant slices are received and processed		
19	Service channel signalling		Service channel signalling is carried by control channel in the super frame. The signal frame size for the control channel is 4096, and the PM-MC symbol length is 1024, modulated with QPSK and coded with punctured 2/3 15360 LDPC for OFDM.		
20	Peak-to-average power ratio (PAPR)		Special active constellation extension (ACE) for APSK constellation as options		
21	Extension Frame		A super frame can include extension frame. The extension frame can be used as NULL signals or for uplink services		

TABLE 1 (end)

## e) TDS Multi-carrier systems (end)

No.	Parameters	6 MHz multi-carrier (OFDM)	7 MHz multi-carrier (OFDM)	8 MHz multi-carrier (OFDM)
22	Payload	3.75-37 Mbit/s with the roll off factor of 0.05, 3.86-38 Mbit/s with the roll off factor of 0.025, depending on FFT-size, modulation, code rate, guard interval	4.38-43.1 Mbit/s with the roll off factor of 0.05, 4.5-44.4 Mbit/s with the roll off factor of 0.025, depending on FFT-size, modulation, code rate, guard interval	5.0-49.31 Mbit/s with the roll off factor of 0.05, 5.14-50.73 Mbit/s with the roll off factor of 0.025, depending on FFT-size, modulation, code rate, guard interval
23	Carrier-to-noise ratio over AWGN channel	Depending on modulation and channel code. 0.62-21.08 dB @ BER=1E-5, for the 7.56 MHz system bandwidth		

APSK: amplitude and phase shift keying

BCH: Bose – Chandhuri – Hocquenghem multiple error correction binary block code

LDPC: low-density parity check

MPE-FEC: multi-protocol encapsulation-forward error correction

NR: nordstrom robinson

OFDM: orthogonal frequency division multiplex

PN-MC: multi-carrier PN-sequence

PRBS: pseudo-random binary sequence

QPSK: quaternary phase shift keying

TMCC: transmission and multiplexing configuration control

VSB: vestigial side band.

(1) Measured value. After RS decoding, error rate  $3 \times 10^{-6}$ .

(2) The  $C/N$  ratios are 9.2 dB for 1/2 rate concatenated trellis coding and 6.2 dB for 1/4 rate concatenated trellis coding.

(3) The 2k mode can be used for single transmitter operation, for single frequency gap-fillers and for small single frequency network. The 8k mode can be used for the same network structures and also for large single frequency network. The 4k mode offers an additional trade-off between transmission cell size and mobile reception capabilities, providing an additional degree of flexibility for network planning of handheld and mobile coverage.

(4) 16-QAM, 64-QAM, MR-16-QAM and MR-64-QAM (MR-QAM: non-uniform QAM constellations), may be used for hierarchical transmission schemes. In this case two layers of modulation carry two different MPEG-2 transport streams. The two layers may have different code rates and can be decoded independently.

(5) In-depth symbol interleaver for the 2k and 4k modes for further improving their robustness in mobile environment and impulse noise conditions.

(6) Pilot carriers are continual pilots, carried by 45 (2k mode) or 177 (8k mode) carriers on all OFDM symbols, and scattered pilots, spread in time and frequency.

(7) For improvement in  $C/N$  performance and Doppler performance in mobile channels.

(8) In order to reduce the average power consumption of the terminal and enabling seamless frequency handover.

(9) TPS pilots carry information on modulation, code rate and other transmission parameters.

(10) The choice of modulation, code rate and guard interval depends on service requirements and planning environment.

(11) Simulated with perfect channel estimation, non-hierarchical modes. Error rate before RS decoding  $2 \times 10^{-4}$ , error rate after RS decoding  $1 \times 10^{-11}$ .

(12) Radio-frequency band segmentation allows use of appropriate modulation and error correction scheme segment by segment, and reception of a centre segment with narrow-band receivers.

- (13) Multi-carrier systems with radio-frequency band segmentation uses 13 segments for television services while any number of segments may be used for other services such as sound services.
- (14) Error rate before RS decoding  $2 \times 10^{-4}$ , error rate after RS decoding  $1 \times 10^{-11}$ .
- (15) The signal frame consists of frame header (FH) and frame body (FB). FH uses pseudo-random binary sequence and single-carrier modulation as both the guard interval and the training sequence for the synchronization as well as channel estimation. FB has 3 744 data and 36 information symbols and could be modulated using either the single-carrier or multi-carrier scheme.
- (16) Error rate after BCH decoding  $3 \times 10^{-6}$ .
- (17) The parameter "Channel occupancy" is related to spectrum limit mask. Recommendation ITU-R SM.1541 provides out-of-band domain emission limits regarded as generic spectrum limit masks, which include digital terrestrial television broadcasting systems. Recommendation ITU-R BT.1206 provides specific spectrum limit masks for digital terrestrial television broadcasting systems for specific environments to enhance compatibility with other radiocommunication services.

## **Attachment 1 to Annex 1**

### **System A Standard**

#### **Bibliography**

ATSC [September, 1996] Recommended Practice A/58. Harmonization with DVB SI in the use of the ATSC digital television standard. Advanced Television Systems Committee.

ATSC [May, 2008] Recommended Practice A/64B. Transmission measurement and compliance for digital television. Advanced Television Systems Committee.

ATSC [November, 2010] Standard A/52:2010. Digital audio compression standard (AC-3, E-AC-3). Advanced Television Systems Committee.

ATSC [April, 2009] Standard A/65:2009. Program and system information protocol for terrestrial broadcasting and cable (PSIP). Advanced Television Systems Committee.

ATSC [May, 2008] Standard A/57B. Content Identification and Labeling for ATSC Transport. Advanced Television Systems Committee.

ATSC [December, 2006] Recommended Practice A/54A. Guide to the use of the ATSC digital television Standard, with Corrigendum No. 1. Advanced Television Systems Committee.

ATSC [April, 2010] Recommended Practice A/74:2010. Receiver performance guidelines. Advanced Television Systems Committee.

ATSC [August, 2009] Standard A/53, Part 1:2009. Digital television system. Advanced Television Systems Committee.

ATSC [January, 2007] Standard A/53, Part 2:2007. RF/Transmission system characteristics. Advanced Television Systems Committee.

ATSC [August, 2009] Standard A/53, Part 3:2009. Service multiplex and transport subsystem characteristics. Advanced Television Systems Committee.

ATSC [August, 2009] Standard A/53, Part 4:2009. MPEG-2 Video system characteristics. Advanced Television Systems Committee.

ATSC [July, 2010] Standard A/53, Part 5:2010. AC-3 Audio system characteristics. Advanced Television Systems Committee.

ATSC [July, 2010] Standard A/53, Part 6:2010. Enhanced AC-3 Audio system characteristics. Advanced Television Systems Committee.

ATSC [November, 2010] Standard A/70, Part 1:2010. Conditional access system for terrestrial broadcast. Advanced Television Systems Committee.

## **Attachment 2 to Annex 1**

### **System B Standard**

#### **Bibliography**

ETSI ETS 300 472. Digital Video Broadcasting (DVB); Specification for conveying ITU-R System B Teletext in DVB bit streams.

ETSI ETR 162. Digital broadcasting systems for television, sound and data services; Allocation of Service Information (SI) codes for Digital Video Broadcasting (DVB) systems.

ETSI ETR 154. Digital Video Broadcasting (DVB); Implementation guidelines for the use of MPEG-2 systems, video and audio in satellite and cable broadcasting applications.

ETSI ETR 211. Digital Video Broadcasting (DVB); Guidelines on implementation and usage of DVB service information.

ETSI ETR 289. Digital Video Broadcasting (DVB); Support for use of scrambling and Conditional Access (CA) within digital broadcasting systems.

ETSI ETS 300 468. Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems.

ETSI ETS 300 743. Digital Video Broadcasting (DVB); Subtitling systems.

ETSI EN 300 744. Digital Video Broadcasting (DVB); Framing structure, channel coding and modulation for digital terrestrial television.

ETSI EN 302 304. Digital Video Broadcasting (DVB); Transmission to Handheld terminals (DVB H).

ETSI EN 301 192. Digital Video Broadcasting (DVB); DVB specification for data broadcasting.

ETSI TS 101 191. Digital Video Broadcasting (DVB); DVB mega-frame for Single Frequency Network (SFN) synchronization.



### **Attachment 3 to Annex 1**

#### **System C Standard**

##### **Bibliography**

ABNT ABNT NBR 15601. Digital terrestrial television – Transmission system.

ABNT ABNT NBR 15602 (Part 1-3). Digital terrestrial television – Video coding, audio coding and multiplexing.

ABNT ABNT NBR 15603 (Part 1-3). Digital terrestrial television – Multiplexing and service information (SI).

ABNT ABNT NBR 15604. Digital terrestrial television – Receivers.

ABNT ABNT NBR 15605. Digital terrestrial television – Security issues.

ABNT ABNT NBR 15606 (Part 1-5). Digital terrestrial television – Data coding and transmission specification.

ABNT ABNT NBR 15607. Digital terrestrial television – Interactivity channel.

ARIB ARIB STD-B10. Service information for digital broadcasting system.

ARIB ARIB STD-B21. Receiver for digital broadcasting.

ARIB ARIB STD-B24. Data coding and transmission specification for digital broadcasting.

ARIB ARIB STD-B25. Conditional access system specifications for digital broadcasting.

ARIB ARIB STD-B31. Transmission system for digital terrestrial television broadcasting.

ARIB ARIB STD-B32. Video coding, Audio coding and multiplexing specifications for digital broadcasting.

### **Attachment 4 to Annex 1**

#### **System D Standard**

##### **Bibliography**

Chinese Standard GB20600-2006. Framing structure, channel coding and modulation for digital television terrestrial broadcasting system.

Chinese Standard GY/T 236-2008. Implementation guidelines for transmission system of digital terrestrial television broadcasting.

Chinese Standard GY/T 237-2008. Frequency planning criteria for digital terrestrial television broadcasting in the VHF/UHF bands.

Chinese Standard GY/T 229.4-2008. Technical specifications and methods of measurement for digital terrestrial television broadcasting transmitters.

Chinese Standard GY/T 229.3-2008. Specification for transport stream multiplexing and interfaces in terrestrial digital television.

Chinese Standard GY/T 229.2-2008. Technical specifications and methods of measurement for digital terrestrial television broadcasting exciter.

Chinese Standard GY/T 229.1-2008. Technical specifications and methods of measurement for digital terrestrial television broadcasting single frequency network adapter.

Chinese Standard GY/T 230-2008. Specification of service information for digital television broadcasting.

Chinese Standard GY/T 231-2008. Specification of electronic programme guide for digital television broadcasting.

Chinese Standard GY/T 238.1-2008. Objective assessment and measurement methods for coverage of digital terrestrial television broadcasting signals Part 1: Single transmitter and outdoor fixed reception.

## **Attachment 5 to Annex 1**

### **System E Standard**

#### **Bibliography**

Chinese Standard GD/J 068-2015. Frame Structure, Channel Coding and Modulation for Digital Television/Terrestrial Multimedia Broadcasting-Advanced (DTMB-A).

## **Attachment 6 to Annex 1**

### **System selection guideline**

The process of selecting a suitable system may be thought of as an iterative one involving three phases:

- Phase I: an initial assessment of which system is most likely to meet the broadcaster's main requirements taking into account the prevailing technical/regulatory environment.
- Phase II: a more detailed assessment of the "weighted" differences in performance.
- Phase III: an overall assessment of the commercial and operational factor impacting the system choice.

Given below is a fuller description of these three phases.

#### **Phase I: Initial assessment**

As a starting point, Table 2 may be used to assess which of the systems would best meet a particular broadcasting requirement.

TABLE 2  
Guideline for the initial selection

Requirements		Suitable systems
Maximum data rate in a Gaussian channel for a given $C/N$ threshold	Required	A, D or E
	Not required	A, B, C, D or E
Maximum ruggedness against multipath interference <sup>(1)</sup>	Required	B, C, D or E
	Not required	A, B, C, D or E
Single frequency networks (SFNs)	Required	B, C, D or E
	Not required	A, B, C, D or E
Mobile reception <sup>(1), (2)</sup>	Required	B, C, D or E
	Not required	A, B, C, D or E
Simultaneous transmission of different quality levels (hierarchical transmission)	Of primary importance	C
	Required	B or C
	Not required	A, B, C, D or E
Independent decoding of data sub-blocks (for example, to facilitate sound broadcasting)	Required	C
	Not required	A, B, C, D or E
Maximum coverage from central transmitter at a given power in a Gaussian environment <sup>(3)</sup>	Required	A, D or E
	Not required	A, B, C, D or E
Maximum ruggedness against impulse interference <sup>(4)</sup>	Required	A, C, D or E
	Not required	A, B, C, D or E

Notes relating to Table 2:

- <sup>(1)</sup> Tradable against bandwidth efficiency and other system parameters.
- <sup>(2)</sup> It may not be possible to provide HDTV reception in this mode.
- <sup>(3)</sup> For all systems in situations with coverage holes, gap filler transmitters will be required.
- <sup>(4)</sup> Systems B and C in 8K mode are applied for this comparison.

## Phase II: Assessment of the weighted differences in performance

After an initial assessment has been made on the basis of Table 2, a more thorough selection process will require comparative evaluation of the performance of the candidate systems. This is the case because the choice of selection parameters itself is not a simple “black or white” selection. In any given situation, any particular criterion will be of greater or lesser significance in the broadcasting environment under study which means that there has to be a means to identify a balance between small differences in performance and more important or less important selection parameters. In other words, it is clear that a small difference between systems against a critical parameter is likely to influence the choice more than large differences against relatively less important selection criteria.

The following methodology is recommended for this phase of system assessment:

*Step 1:* requires the identification of performance parameters that are relevant to the circumstances of the administration or broadcaster wishing to choose a DTTB system. These parameters might include the inherent performance capabilities of the digital system in itself, its compatibility with existing analogue services and the need for interoperability with other image communications or broadcasting services.

*Step 2:* requires the assignment of “weights” to the parameters in order of importance or criticality to the environment in which the digital TV service is to be introduced. This weighting might be a simple multiplier such as 1 for “normal” and 2 for “important”.

*Step 3:* involves the accumulation of test data from (preferably both) laboratory and field trials. This data can be gathered direct by the parties involved in the evaluation or may be obtained from others who have undertaken trials or evaluations. It is expected that Radiocommunication Study Group 6 (formerly Study Group 11) will, in the near future, prepare a report providing full technical evidence on the different DTTB systems, which may be used where adequate test data is not available from other reliable sources.

*Step 4:* then requires the matching of test data with performance parameters and the determination of a “rating” against each parameter. The overall rating is used to choose a system that best matches the requirements. A tabular structure that uses a simple numerical rating and weighting scale has been found useful by some administrations. It is taken as a “given” that all candidate systems are able to provide a viable DTTB service. Accordingly, the differences between systems will be relatively small. It is desirable to avoid unnecessary exaggeration of the differences but, at the same time, take care to ensure that the selection process is matched to the needs of the intended service. A simple and compact numerical rating scale can be one way to achieve these goals.

The following scales are examples that might be useful:

<b>Performance</b>	<b>Rating</b>
Satisfactory	1
Better	2
Best	3

In this scale a 0 (or null) value is given for a system that does not provide satisfactory performance against a given parameter or for a parameter that is unable to be evaluated.

<b>Importance</b>	<b>Weighting</b>
Normal	1
Significant	2
Critical	3

The following is an example of a tabular structure that might be used for comparative assessment of various systems.

No.	Criterion	System performance					Weighting	System rating				
		A	B	C	D	E		A	B	C	D	E
1	Characteristics of transmitted signals											
A	Robustness of signal											
	Immunity of electrical interference											
	Efficiency of transmitted signal											
	Effective coverage											
	Reception using indoor antenna											
	Adjacent channel performance											
	Co-channel performance											
B	Resilience to distortions											
	Resilience to multipath distortions											
	Mobile reception											
	Portable reception											

### Phase III: Assessment of commercial and operational aspects

The final phase is an assessment of the commercial and operational aspects to ascertain which of the systems is indeed the best solution overall. Such an assessment will take into account the required timescales to service implementation, cost and availability of equipment, interoperability within an evolving broadcasting environment, etc.

#### Compatible receiver

In the cases where it is necessary to receive more than one modulation system option, compatible receivers will be needed. The cost of such receivers, taking into account the progress in digital technologies, should not be significantly more than receivers for a single modulation system, but the advantages of such receivers could be important. They may open the door to attractive additional possibilities and services for the consumer and broadcaster as indicated by Table 2. Studies continue on this matter.

---